

EconoVue® Clear Interior

Perforation pattern:

Approx. 60/40 (40% open)

Perforation size:

Approx. 0.062 in. (1.6 mm)

Film:

Approx. 6.5-mil clear calendered PVC on a 3-in. core

Standard roll sizes:

54 in. x 100 ft.


Application:

POP, retail & commercial window graphics designed for interior mounting

Product code:

CFEVISL/CFEVIWL





Interior Mount Product Specifications

Product Code: CFEVISL/CFEVIWL

6.5-mil clear PVC with clear removable acrylic pressure-sensitive adhesive. Available with an unperforated solid paper release liner (CFEVISL), or a white PET liner (CFEVIWL) consisting of white PET film laminated to perforated paper to absorb ink.

Applications	POP, retail and other graphics for interior mounting on windows, glass doors and other transparent surfaces. <i>Not recommended for use on tinted windows.</i>
Composition	Clear PVC with clear pressure-sensitive adhesive coating and an unperforated solid paper liner or a white PET liner.
Open Area	40%, approx.
Vinyl Thickness (incl. adhesive)	6.5 mils (.0065 in./165 microns), approx.
Release Liner Thickness	Solid paper liner: 7 mils (.007 in./178 microns), approx. White PET liner: 5.5 mils (.0055 in./140 microns), approx.
Adhesive Thickness	1 mil (.001 in./25 microns), approx.
Perforation Diameter	.062 in. (1.6 mm), approx.
Standard Width/Length	54 in. x 100 ft. (1.37 x 30.48 m)
Dimensional Stability	Good
Minimum Application Temperature	40° F (4° C)
Service Temperature Range	0° F to 140° F (-17° C to 60° C)
Expected Lifetime	1 year. 6 months for clean removal. Adhesion may increase with time.
Water Resistance	Fair. Immersion in water not recommended.
Humidity Resistance	Fair
Solvent Resistance	Good
Storage Stability	1-year shelf life when stored at 70° F (21° C) and 50% relative humidity.
Printing	Print on clear film, not on liner. Designed for screen printing, UV-cure printing or other method that allows printing mirror image with the color sequence printed in reverse, followed by the application of a full coat of white ink and then a full coat of black ink to achieve one-way visibility. Recommended ink temperature: 65° to 82° F (18° to 28° C), approx. For UV-cure printing, choose the white PET liner. For a softer, more translucent effect without one-way visibility, it is possible to print normally without adding the white and black coats of ink. In this case, any text will display in reverse on one side.
Installation	Apply to clean, dry glass surface. Use mild soap and water, rinse and dry glass well. Do NOT use ammonia, Windex® or other solvent-based glass cleaners prior to application.
Removal	Remove by peeling from surface. Remove any adhesive residue on older installations, if necessary.

Subject to change without notice

It is the responsibility of purchasers to independently verify, prior to use, the suitability of the products for their specific applications and print methods. CLEAR FOCUS cannot be held liable for any misuse, damage or losses as specified in its product warranty.

Distributed by:



ATLANTA
800-241-6049
678-602-4140
FAX: 678-602-4139

BOSTON
781-749-4590
FAX: 781-740-2866

CHICAGO
800-654-1357
630-543-4600
FAX: 630-543-0856

DALLAS
800-338-2241
817-477-4770
FAX: 817-473-4515

LOS ANGELES
800-825-4846
909-923-1879
FAX: 909-923-4079

MIAMI
800-432-5068
954-971-0436
FAX: 954-971-9218

NEW YORK/NEWARK
973-589-7800
212-962-6565
FAX: 973-589-3225

PHILADELPHIA
800-222-0146
856-662-3373
215-462-3636
FAX: 856-486-4552

TORONTO
888-460-4406
905-953-9393
FAX: 905-953-1331