# Q4505B Matte Work & Turn

Aqueous Coating Technical Data Sheet

The Prisco Q4505B is a matte work & turn coating for inline application wet trapping over lithographic inks to both sides of the substrate. It is designed to produce an even and fast drying film formation over a wide variety of substrates and inks. This allows for quick turnaround times and an even defect-free surface. This product is a matte version of our Q5515B Satin coating.

### Advantages:

- Superior matte finish
- Good leveling
- Minimizes burnishing and marring
- Good Rub Resistance
- Can be over-coated with:
  - UV coatings 0
  - 0 Oleo resinous varnishes
  - Aqueous coatings 0
- Displays adhesion to:
  - Plastic film laminates. 0
  - Hot foil stamping. 0
  - Glue 0
  - Laser imprinting

## **Physical Properties:**

Viscosity 17-19 seconds, #3 EZ Zahn timed @ 25°C/77°F

Hq 8.0-9.0 Gloss 10

Solids 38% +/-3% 8.6-8.8 lbs/gal Wt./gal

**Block Resistance** Pass 120°F, 10PSI, 6 Hrs

Rub Resistance Good @ 200+ Sutherland Rubs w/ 4lb weight

#### Application:

Commercial Sheetfed General Purpose **Folding Carton** 

- Application Viscosity-Stir and use as received.
  - Viscosity reduction only with Prisco technical support
  - Recommended application temperature 70-80°F
- Equipment-Blanket and tower coaters, anilox coaters
- Drying-Sufficient volumes or warm dry air, and medium and short wave IR. Pile temperatures should range 95-100°F 1st side, and 85-90°F 2<sup>nd</sup> side
- Wet Film Weight-Recommend 0.8-1.2 wet pounds per 1000 square feet of substrate
- Inks-Sheetfed lithographic oxidative ink. Wax content should be limited to 2-3% polyethylene.
- Clean up-Cleaning is best before coating dries. Use warm water and Prisco Aqueous Coating Cleaner
- Shelf Life-6 months stored at room temperature.

Product Code: RP85-55B (55 gallon drum), RP85-30B (30 gallon drum), RP85-5GF (5 gallon pail)

Prisco recommends that you test coatings for specialty applications using the actual raw materials to be used in production prior to printing.

Read MSDS before using this product

## An ISO 9001:2008 Registered Facility

PRINTERS' SERVICE

26 Blanchard Street Newark, New Jersey 07105 (212) 962-6565 • (973) 589-7800 FAX (973) 589-3225

www.prisco.com

ATLANTA

**BOSTON** 

781-749-4590

FAX: 781-740-2866

800-241-6049 404-876-1234 FAX: 404-873-2917

630-543-4600 FAX: 630-543-0856 DALLAS

CHICAGO

800-654-1357

800-338-2241 817-477-4770 FAX: 817-473-4515 LOS ANGELES 800-825-4846 909-923-1879 FAX: 909-923-4079

800-432-5068

954-385-1975

FAX: 954-385-8875

MIAMI

212-962-6565 PHILADELPHIA

973-589-7800

NEW YORK/NEWARK

800-222-0146 856-662-3373 215-462-3636 FAX: 856-486-4552 PRISCO CANADA TORONTO 888-460-4406 905-953-9393 FAX: 905-953-1331

**Product Bulletin** 

PRISCO EUROPE (U.K.) 44(0)1423 810 320 FAX: 44(0)1423 810 319 PRISCO EUROPE (Continent) 32(0)56 42 35 97