


GRAPHTEC

Graphtec America, Inc.

FC8600 SERIES HIGH PERFORMANCE CUTTING PLOTTERS

ARMS (5th Gen. Auto Registration Mark Sensor)



Max cutting force up to 600 grams | Max cutting speed of 58.5" per second

Interface: USB 2.0, Serial RS-232C and Ethernet


3" LCD screen | Servo Motor

Three-step push roller settings


Perforation cutting channel

Tangential Emulation

Mac & Windows compatible



Perforation Cutting



Expanded Contour Cutting Area

Contour cut prismatic grade reflective sheeting media






5 Sizes

FC8600-160 (64") | FC8600-130 (54") | FC8600-100 (42")

FC8600-75 (30") | FC8600-60 (24")

Includes: Stand, media catch basket, rear media rollers, Graphtec Studio software & Cutting Master3 plug-in for Illustrator & CorelDraw (Macintosh & Windows compatible)





5 Cutting Sizes: 24" | 30" | 42" | 54" | 64"

FC8600 SERIES TECHNICAL SPECIFICATIONS

ITEM	FC8600-60	FC8600-75	FC8600-100	FC8600-130	FC8600-160
Maximum Cutting Area	24 in x 164 ft (610 mm x 50 m)	30 in x 164 ft (762 mm x 50 m)	42 in x 164 ft (1067 mm x 50 m)	54 in x 164 ft (1372 mm x 50 m)	64 in x 164 ft (1625 mm x 50 m)
Compatible Media Widths	2 in to 30.3 in (50 mm to 770 mm)	2 in to 36.2 in (50 mm to 919 mm)	2 in to 48.2 in (50 mm to 1224 mm)	2 in to 60.2 in (50 mm to 1529 mm)	2 in to 72.5 in (50 mm to 1841 mm)
Maximum Media Thickness	59.1 mil (1.48 mm)				
Maximum Cut Speed	58.5 in/s (1485 mm/s) diagonal				
Programmable Cutting Force	20 gf - 600 gf in 48 steps				
Sheet Cutter Max Thickness	11 mil including media release liner (backing)				
Programmable Resolution	GP-GL™: 0.1/.05/.025/.01mm; HP-GL®: 0.001 in (0.025mm); GP-GL™: 254, 508, 1016, 2540; HP-GL®: 1016				
Compatible Media Types	Self-adhesive vinyl film, diamond grade ⁽¹⁾ , fluorescent film, reflective film, Amberlith™, Rubylith™, sandblast resist rubber, high-intensity reflective film ⁽¹⁾ , prismatic reflective sheeting ⁽¹⁾ , window tint film, paint protection film ⁽¹⁾ , automotive paint protection film ⁽¹⁾ , etc.				
Interface	USB 2.0 High-speed / Serial RS-232C / Ethernet interface				
ARMS	5th Generation Advanced Registration Mark Sensing System				
Command Modes	GP-GL™, HP-GL® (Selectable in command menu or auto detection)				
Display Panel	3" graphic LCD with comprehensive icon-corresponding soft keys				
Shipping Weight with Stand	106 lbs (48 kg)	115 lbs (52 kg)	133 lbs (60 kg)	150 lbs (68 kg)	161 lbs (73 kg)
Unit Dimensions with Stand	44 x 28 x 48 in (1120 x 711 x 1219 mm)	50 x 28 x 48 in (1270 x 711 x 1219 mm)	61.8 x 28 x 48 in (1570 x 711 x 1219 mm)	73.6 x 28 x 48 in (1870 x 711 x 1219 mm)	84 x 28 x 48 in (2130 x 711 x 1219 mm)
Warranty	2 Years Parts & Labor Plus 1 Additional Year after online registration @www.graphtecamerica.com				

1) Additional (optional) push rollers may be required.

Software Included: Graphtec Studio (Mac & Windows)

Software Plug-in Included: Cutting Master 3 for Adobe Illustrator (Mac & Windows), CorelDraw (Windows)



Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.

GRAPHTEC

Graphtec America, Inc.
17462 Armstrong Avenue
Irvine, CA 92614

WEBSITE GRAPHTECAMERICA.COM

Prisco digital

www.prisco.com/priscodigital
pdsales@prisco.com