



26 Blanchard Street | Newark NJ 07105 | (973) 589-7800 | www.prisco.com

# PRISCO<sup>®</sup> E-Cure H-UV-893 Gloss Dry Erase H-UV Coating

#### **Product Description:**

The Prisco E-Cure H-UV-893 is a high gloss H-UV coating for inline application over H-UV inks and a variety of substrates. It is designed to produce an even and fast curing film formation with a superior gloss finish that allows for Dry Erase Marker application. This allows for quick turnaround times and an even defect-free surface. This product is designed to have excellent flexibility, adhesion properties, gloss depth, and clarity. The E-Cure H-UV-893 has been field tested and approved on the H-UV Komori press. It has good cure response with minimal to no surface tack or yellowing. Results may vary depending H-UV system.

#### Advantages:

- Superior gloss levels, excellent flexibility and scratch resistance
- Good cure response, Rub and Taber resistance
- Low odor, low VOC, non-yellowing
- Dry Erase, Imprintable, Stampable

#### **Physical Properties:**

- Viscosity (cps) \_\_\_\_\_ 225-300 cps, Brookfield LV Viscometer @ 25°C/77°F
- Viscosity (seconds) \_\_\_\_30-38 seconds #3 Zahn Cup @ 25°C/77°F
- Gloss\_\_\_\_\_>85
- Wt./gal \_\_\_\_\_9.3 lbs/gal
- Cure \_\_\_\_\_\_ H-UV "D" Bulb, High @ 100 fpm (tested in controlled lab conditions w/ UVEXS Cure Unit)
- MEK Rubs\_\_\_\_\_ 15-25 Double Rub

### **Application (Sheetfed and Flexo)**

- Application Viscosity Stir well. Keep covered and reduce light exposure when using.
- Equipment Blanket and tower coaters, anilox coaters
- Curing Sufficient amount of focused H-UV energy depending on press, press speed, and energy capability.
- Inks H-UV Ink, primed or oxidized conventional sheetfed inks.
- Clean Up Prisco UV Cleaner
- Shelf Life 6 months stored at room temperature. Keep away from heat >100°F and minimize the products exposure to light.

## Product Code: READ SDS BEFORE USING THIS PRODUCT

RI85-55A (55 gallon drum), RI85-30A (30 gallon drum), RI85-5GB (5 gallon pail), RI85-ACT (275 gallon Tote)



Prisco recommends that you test coatings for specialty applications using the actual raw materials to be used in production prior to printing.

 Atlanta

 Support:
 678-601-4140

 Orders:
 800-241-6049

#### Boston 781-749-4590 800-222-0146

Chicago 630-543-4600 800-241-6049 **Dallas** 817-477-4770 800-241-6049 Los Angeles 909-923-1879 800-825-4846 Miami 954-971-0436 800-241-6049

Australia 61 2 4702 1211

 Newark

 Support:
 973-589-7800

 Orders:
 800-222-0146

Philadelphia 856-662-3373 800-222-0146

**Belgium** +32 56 40 41 82 **United Kingdom** +32 56 40 41 82 **Toronto** 905-953-9393 888-460-4406