



Q9001B Low VOC Satin Work & Turn

Aqueous Coating Technical Data Sheet

The Prisco Q9001B is a general purpose satin work & turn coating for inline application wet trapping over lithographic inks to both sides of the substrate. It is designed to produce an even and fast drying film formation over a wide variety of substrates and inks. This allows for quick turnaround times and an even defect-free surface. This product has been formulated to have LOW VOC content. It is part of the Prisco "Go Green" Package, especially designed for printers' in areas where air quality management is a concern. This product is the satin version of our Q9000B.

Advantages:

- Smooth Satin Finish
- Good Rub Resistance
- Good Dry
- Low VOC 0.05 lbs/gal (0.57%)
- Zinc and IPA Free

Physical Properties:

Viscosity	17-19 seconds, #3 EZ Zahn timed @ 25°C/77°F
pH	7.5-8.5
Gloss	@ 20-30
Solids	38% +/-3%
Wt./gal	8.6-8.8 lbs/gal
VOC	0.05 lbs per gallon
Block Resistance	Pass 120°F, 10PSI, 6 Hrs
Rub Resistance	Good @ 200+ Sutherland Rubs w/ 4lb weight

Application:

- Commercial Sheetfed
- General Purpose
- Folding Carton
- **Application Viscosity**-Stir and use as received.
 - Viscosity reduction only with Prisco technical support
 - Recommended Application Temperature 70-80°F
- **Equipment**-Blanket and tower coaters, anilox coaters
- **Drying**-Sufficient volumes of warm dry air, and medium and short wave IR. Pile temperatures should range 95-100°F 1st side, and 85-90°F 2nd side
- **Wet Film Weight**-Recommend 0.8-1.2 wet pounds per 1000 square feet of substrate
- **Inks**-Sheetfed lithographic oxidative ink. Wax content should be limited to 2-3% polyethylene.
- **Clean up**-Cleaning is best before coating dries. Use warm water and Prisco Aqueous Coating Cleaner
- **Shelf Life**-6 months stored at room temperature.

Product Code: RU02-55B (55 gallon drum), RU02-30B (30 gallon drum), RU02-5GF (5 gallon pail)

Prisco recommends that you test coatings for specialty applications using the actual raw materials to be used in production prior to printing.

Read MSDS before using this product

an ISO 9001:2008 Registered Facility



Atlanta
Support: 678-601-4140
Orders: 800-211-6019

Boston
781-749-4590
800-222-0146

Chicago
630-543-4600
800-211-6019

Dallas
817-477-4770
800-211-6019

Los Angeles
909-923-1879
800-825-1846

Miami
954-971-0436
800-211-6019

Newark
Support: 973-589-7800
Orders: 800-222-0146

Philadelphia
856-662-3373
800-222-0146

Belgium
+32 56 40 41 82

United Kingdom
+32 56 40 41 82

Toronto
905-953-9393
888-160-1106

Australia
61 2 4702 1211